

UHU®

POWER SPRAY ADHESIVE PERMANENT & TRANSPARENT

POWER SPRAY ADHESIVE PERMANENT & TRANSPARENT



APPLICATION

Directions for use:

Shake can well before use. Spray from a distance of approx. 15-20 cm to achieve even application. Spray the parts to be joined separately, leave to dry for approx 5-20 minutes, then press together briefly and very firmly. If gluing Styrofoam®, thinly spray both surfaces from a distance of approx. 30 cm and leave to dry for approx. 5-20 minutes before joining together.

Stains/residue: For cleaning smudgy parts and equipment as well as for removing stains use cleaning spirit (test first). Cured adhesive stains are hard to remove.

Points of attention: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Throw away only when completely empty. Do not breathe vapour. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition – Do not smoke. Without adequate ventilation accumulation of potentially explosive alloys possible. Keep out of reach of children.

STORAGE CONDITIONS

Product should be stored in a dry, cool and frost free place.

PRODUCT DESCRIPTION

Power Spray Adhesive Permanent & Transparent is a universal and transparent contact spray adhesive for small and large surfaces. Glues fast, strong and clean various materials, also suitable for Styrofoam®. The extra smooth and even spray pattern enables economical usage. Non-clog spray valve.

FIELD OF APPLICATION

For bonding paper, cardboard, leather, felt, foams, many plastics, fabrics, textiles, Styrofoam® etc. among themselves and to many other materials such as wood, ceramics, glass etc. Suitable for indoor use only.

Not suitable for PE, PTFE or silicone, as these plastics have anti-adhesive properties.

PROPERTIES

- Universal
- Transparent and permanent
- Strong, fast and clean
- Also suitable for Styrofoam®
- Extra smooth and even spray pattern

PREPARATION

Working Conditions: Do not use at temperatures below +10 °C.

Personal safety: Power Spray Adhesive Permanent & Transparent contains volatile, highly flammable solvents. Appropriate precautions should be taken when using and storing this product. When applying product to larger surfaces, ensure good ventilation in the working area.

Surface Requirements: The areas to be glued must be dry and free of any dust or grease.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.